


SUPRAMID

BLACK



Type	Twisted and coated multifilament Sizes 5/0 and 6/0 monofilament
Composition	Polyamide 6.6 strands enclosed in a polyamide 6 sheet
Colour	Black
Tissue reaction	Minimal
Absorption	Non absorbable, gradually encapsulated by connective tissue
Presentation	Box with 12 sutures

*For quality
&
safety*

smi

www.sutures.be

SUPRAMID

BLACK

CHARACTERISTICS

- High tensile strength, non absorbable
- Synthetic
- Twisted structure

- Multifilament in a sheath

- Pliability and softness

- Hermetically sealed packing

INDICATIONS General soft tissue closing
 and/or ligation
especially in Skin closure

BENEFITS

Excellent and permanent tissue support






Minimal tissue reaction




Excellent handling properties
High flexibility
High tensile strength
Excellent knot security







Soft passage through the tissues without sawing,
tissue drag and trauma
Good knot tie down / adjustability
Reduced capillary action





Good handling properties
Easy and secure knotting




Guaranteed seal and product sterility










 Round bodied taper point		Metric	USP	Length	Order number
1/2 circle 	HR 16 mm 	1.5	4/0	75 cm	<i>black</i> 4150116
		2	3/0	75 cm	<i>black</i> 4200116
	HR 20 mm 	2	3/0	45 cm	<i>black</i> 4200120
		HR 26 mm 	3	2/0	75 cm




 Round bodied taper point		Metric	USP	Length	Order number
Straight 	GR 22 mm 	1.5	4/0	50 cm	<i>black</i> 4152022




 Reverse cutting		Metric	USP	Length	Order number
1/2 circle 	HS 17 mm 	1.5	4/0	75 cm	<i>black</i> 4151417
		2	3/0	75 cm	<i>black</i> 4201417
	HS 20 mm 	1	5/0	75 cm	<i>black</i> 4101420
		1.5	4/0	75 cm	<i>black</i> 4151420
	HS 22 mm 	2	3/0	75 cm	<i>black</i> 4201420
		1.5	4/0	75 cm	<i>black</i> 4151422
	HS 26 mm 	2	3/0	75 cm	<i>black</i> 4201422
		2	3/0	75 cm	<i>black</i> 4201422
	2	3/0	75 cm	<i>black</i> 4201426	
	3	2/0	75 cm	<i>black</i> 4301426	

 Cutting		Metric	USP	Length	Order number
Straight 	GS 20 mm 	1.5	4/0	50 cm	<i>black</i> 4152120
	GS 25 mm 	1.5	4/0	60 cm	<i>black</i> 4152125

 Reverse cutting		Metric	USP	Length	Order number
3/8 circle 	DS 12 mm 	0.7	6/0	75 cm	<i>black</i> 4071512
		1	5/0	45 cm	<i>black</i> 4101512-45
		1	5/0	75 cm	<i>black</i> 4101512
		1.5	4/0	45 cm	<i>black</i> 4151512

 Reverse cutting		Metric	USP	Length	Order number
	DS 16 mm 	0.7	6/0	75 cm	<i>black</i> 4071516
		1	5/0	45 cm	<i>black</i> 4101516-45
		1	5/0	75 cm	<i>black</i> 4101516
		1.5	4/0	45 cm	<i>black</i> 4151516
		1.5	4/0	75 cm	<i>black</i> 4151516-75
		2	3/0	45 cm	<i>black</i> 4201516
		2	3/0	75 cm	<i>black</i> 4201516-75
	DS 16 mm black 	1	5/0	75 cm	<i>black</i> 4101516VB
	DS 19 mm 	0.7	6/0	75 cm	<i>black</i> 4071519
		1	5/0	75 cm	<i>black</i> 4101519
		1.5	4/0	45 cm	<i>black</i> 4151519
		1.5	4/0	75 cm	<i>black</i> 4151519-75
		2	3/0	75 cm	<i>black</i> 4201519
		3	2/0	75 cm	<i>black</i> 4301519
DS 19 mm Easy Pass 	1.5	4/0	75 cm	<i>black</i> 4151519P-75	
DS 19 mm black 	1	5/0	75 cm	<i>black</i> 4101519VB	
	1.5	4/0	75 cm	<i>black</i> 4151519VB	
DS 24 mm 	2	3/0	75 cm	<i>black</i> 4201524	
	3	2/0	75 cm	<i>black</i> 4301524	
	3.5	0	75 cm	<i>black</i> 4351524	
DS 36 mm 	3	2/0	75 cm	<i>black</i> 4301536	
	3.5	0	75 cm	<i>black</i> 4351536	
		4	1	75 cm	<i>black</i> 4401536

 Round bodied taper cutting point		Metric	USP	Length	Order number
	HRT 18 mm 	1.5	4/0	75 cm	<i>black</i> 4150518
		2	3/0	75 cm	<i>black</i> 4200518

 Round bodied taper cutting point		Metric	USP	Length	Order number
	DRT 18 mm 	1.5	4/0	75 cm	<i>black</i> 4150418
		2	3/0	75 cm	<i>black</i> 4200418