


SUPRAMID

BLACK



Type	Twisted and coated multifilament Sizes 5/0 and 6/0 monofilament
Composition	Polyamide 6.6 strands enclosed in a polyamide 6 sheet
Colour	Black
Tissue reaction	Minimal
Absorption	Non absorbable, gradually encapsulated by connective tissue
Presentation	Box with 12 sutures; Cassette



*For quality
&
safety*

smi

www.sutures.be

SUPRAMID

BLACK

CHARACTERISTICS

- ✓ High tensile strength, non absorbable
- ✓ Synthetic
- ✓ Twisted structure

- ✓ Multifilament in a sheath

- ✓ Pliability and softness

- ✓ Hermetically sealed packing

INDICATIONS General soft tissue closing
 and/or ligation
especially in Skin closure

BENEFITS

- Excellent and permanent tissue support






- Minimal tissue reaction




- Excellent handling properties
High flexibility
High tensile strength
Excellent knot security







- Soft passage through the tissues without sawing,
tissue drag and trauma
Good knot tie down / adjustability
Reduced capillary action





- Good handling properties
Easy and secure knotting




- Guaranteed seal and product sterility










 Round bodied taper point		Metric	USP	Length	Order number
1/2 circle 	HR 16 mm 	1.5	4/0	75 cm	<i>black</i> 4150116
		2	3/0	75 cm	<i>black</i> 4200116
	HR 20 mm 	2	3/0	45 cm	<i>black</i> 4200120
		HR 26 mm 	3	2/0	75 cm




 Round bodied taper point		Metric	USP	Length	Order number
Straight 	GR 22 mm 	1.5	4/0	50 cm	<i>black</i> 4152022




 Reverse cutting		Metric	USP	Length	Order number
1/2 circle 	HS 17 mm 	1.5	4/0	75 cm	<i>black</i> 4151417
		2	3/0	75 cm	<i>black</i> 4201417
	HS 20 mm 	1	5/0	75 cm	<i>black</i> 4101420
		1.5	4/0	75 cm	<i>black</i> 4151420
	HS 22 mm 	2	3/0	75 cm	<i>black</i> 4201420
		1.5	4/0	75 cm	<i>black</i> 4151422
	HS 26 mm 	2	3/0	75 cm	<i>black</i> 4201422
		2	3/0	75 cm	<i>black</i> 4201422
	2	3/0	75 cm	<i>black</i> 4201426	
	3	2/0	75 cm	<i>black</i> 4301426	

 Cutting		Metric	USP	Length	Order number
Straight 	GS 20 mm 	1.5	4/0	50 cm	<i>black</i> 4152120
	GS 25 mm 	1.5	4/0	60 cm	<i>black</i> 4152125

 Reverse cutting		Metric	USP	Length	Order number
3/8 circle 	DS 12 mm 	0.7	6/0	75 cm	<i>black</i> 4071512
		1	5/0	45 cm	<i>black</i> 4101512-45
		1	5/0	75 cm	<i>black</i> 4101512
		1.5	4/0	45 cm	<i>black</i> 4151512

 Reverse cutting		Metric	USP	Length	Order number
	DS 16 mm 	0.7	6/0	75 cm	<i>black</i> 4071516
		1	5/0	45 cm	<i>black</i> 4101516-45
		1	5/0	75 cm	<i>black</i> 4101516
		1.5	4/0	45 cm	<i>black</i> 4151516
		1.5	4/0	75 cm	<i>black</i> 4151516-75
		2	3/0	45 cm	<i>black</i> 4201516
		2	3/0	75 cm	<i>black</i> 4201516-75
	DS 16 mm black 	1	5/0	75 cm	<i>black</i> 4101516VB
	DS 19 mm 	0.7	6/0	75 cm	<i>black</i> 4071519
		1	5/0	75 cm	<i>black</i> 4101519
		1.5	4/0	45 cm	<i>black</i> 4151519
		1.5	4/0	75 cm	<i>black</i> 4151519-75
		2	3/0	75 cm	<i>black</i> 4201519
		3	2/0	75 cm	<i>black</i> 4301519
DS 19 mm Easy Pass 	1.5	4/0	75 cm	<i>black</i> 4151519P-75	
DS 19 mm black 	1	5/0	75 cm	<i>black</i> 4101519VB	
	1.5	4/0	75 cm	<i>black</i> 4151519VB	
DS 24 mm 	2	3/0	75 cm	<i>black</i> 4201524	
	3	2/0	75 cm	<i>black</i> 4301524	
	3.5	0	75 cm	<i>black</i> 4351524	
DS 36 mm 	3	2/0	75 cm	<i>black</i> 4301536	
	3.5	0	75 cm	<i>black</i> 4351536	
		4	1	75 cm	<i>black</i> 4401536

 Round bodied taper cutting point		Metric	USP	Length	Order number
	HRT 18 mm 	1.5	4/0	75 cm	<i>black</i> 4150518
		2	3/0	75 cm	<i>black</i> 4200518

 Round bodied taper cutting point		Metric	USP	Length	Order number
	DRT 18 mm 	1.5	4/0	75 cm	<i>black</i> 4150418
		2	3/0	75 cm	<i>black</i> 4200418

IN CASSETTES

Metric	USP	Length	Order number
1.5	4/0	100 m	4015
2	3/0	100 m	4020
3	2/0	100 m	4030
3.5	0	100 m	4035
4	1	100 m	4040
5	2	75 m	4050
6	3&4	50 m	4060
7	5	40 m	4070
8	6	40 m	4080
9	7	30 m	4090

